

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial product name: Q-Coat Water Repellent Penetrating Sealer

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / preparation:
Industrial.
building protective agent , waterproofing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer: Synergy Buildings
Street/POB-No.: Supplies 236 Planet St
State/postal code/city: Welshpoo, WA, 6106
Telephone: +61 1300 655 853

Distributor: Synergy Buildings
Street/POB-No.: Supplies 236 Planet St
State/postal code/city: Welshpoo, WA, 6106
Telephone: +61 1300 655 853

Information about the Safety Data Sheet:

Telephone	+61 1300 655 853
eMail	info@oxide.com.au

1.4 Emergency telephone number

Emergency Information: **+61 1300 655 853**

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Non-Hazardous Chemical according to Australian GHS criteria. Non-Dangerous Goods to the ADG Code.

Hazard class	Hazard category	Route of exposure
Long-term (chronic) aquatic hazard	Category 3	

2.2 Label elements

Signal Word: Exempt

H-Code	Hazard Statements
H412	Harmful to aquatic life with long lasting effects.
P-Code	Precautionary Statements
P273	Avoid release to the environment.
P501	Dispose of contents/container to waste disposal.

Code	Additional Labelling
EUH208	Contains chloromethylisothiazolinone and methylisothiazolinone (3:1), aminopropyltriethoxysilane. May produce an allergic reaction.

2.3 Other hazards

The product hydrolyses under formation of ethanol (CAS-Nr. 64-17-5). Ethanol is classified concerning both physical and health hazards. The hydrolysis rate and consequently the relevance for the hazard profile of the product is strongly dependent on the specific conditions.

SECTION 3: Composition/information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

3.2.1 Chemical characteristics

Alkoxy silanes + siloxane + water

3.2.2 Ingredients

Type	CAS No.	Substance	Content %
INHA	112-02-7	Hexadecyltrimethylammoniumchloride	<1
INHA	919-30-2	3-Aminopropyltriethoxysilane	<0.5

Type: INHA: ingredient, VERU: impurity

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above $\geq 0.1\%$.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In case of accident or if you feel unwell seek medical advice (show label or SDS where possible).

After contact with the eyes:

Rinse immediately with plenty of water. Seek medical advice in case of continuous irritation.

After contact with the skin:

Wash with plenty of water or water and soap. In the event of a visible skin change or other complaints, seek medical advice (show label or SDS where possible).

After inhalation:

Provide fresh air.

After swallowing:

Give several small portions of water to drink. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

4.3 Advice for the doctor:

Further toxicology information in section 11 must be observed.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

not applicable

Extinguishing media which must not be used for safety reasons:

not applicable

5.2 Special hazards arising from the substance or mixture

Ambient fire may lead to hazardous fumes. Exposure to combustion products may be a health hazard! Hazardous combustion products: toxic and very toxic fumes .

5.3 Advice for firefighters

Special protective equipment for fire fighting:

Use respiratory protection independent of recirculated air. Keep unprotected persons away.

General information:

Product does not burn. Use extinguishing measures appropriate to the source of the fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material.

6.2 Environmental precautions

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

6.3 Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

Further information:

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Observe notes under section 7.

6.4 Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

SECTION 7: Handling and storage

7.1 Precautions for safe handling

General information:

Always stir well before use.

Precautions for safe handling:

Ensure adequate ventilation. Must be syphoned off in situ. Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Keep away from incompatible substances in accordance with section 10. Observe information in section 8.

Precautions against fire and explosion:

Product may release ethanol. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

7.2 Conditions for safe storage, including any incompatibilities

Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place. Protect against sun. Protect against frost. Store container in a well ventilated place.

Minimum temperature allowed during storage and transportation: 0 °C

Do not allow this material to freeze.

Maximum temperature allowed during storage and transportation: 40 °C

7.3 Specific end use(s)

No data available.

7.4 Regulations and standards (Australia):

Store and handle in accordance with Work Health & Safety Regulations or Occupational Health & Safety Regulations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Maximum airborne concentrations at the workplace:

CAS No.	Substance	Type	mg/m ³	ppm	Dust fract.	Fibre/m ³
	Aerosol - inhalable fraction		10.0			
64-17-5	Ethanol	ES AU	1900.0	1000.0		

The aerosol limit specified is a recommendation should aerosol be formed during processing.

8.2 Exposure controls

8.2.1 Exposure in the work place limited and controlled

General protection and hygiene measures:

Observe standard industrial hygiene practices for the handling of chemical substances. Do not inhale gases/vapours/aerosols. Use with adequate ventilation. Do not eat, drink or smoke when handling.

Personal protection equipment:

Respiratory protection

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136.

Recommended Filter type: Combined filter type ABEK-P2 (certain inorganic, organic and acidic gases and vapors; ammonia/amines; particles), according to acknowledged standards such as EN 14387

If inhalative exposure above the occupational exposure limit cannot be excluded, adequate respiratory protection equipment must be used. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136. Recommended Filter type: Gas filter type ABEK (certain inorganic, organic and acidic gases and vapors; ammonia/amines), according to acknowledged standards such as EN 14387

Observe the equipment manufacturer's information and wear time limits for respirators.

Eye protection

Recommendation: protective goggles .

Hand protection

Use of protective gloves is recommended when handling the material.

Recommended glove types: Protective gloves made of butyl rubber
thickness of the material: > 0.3 mm
Breakthrough time: > 480 min

Recommended glove types: Protective gloves made of nitrile rubber
thickness of the material: > 0.1 mm
Breakthrough time: > 480 min

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Note that, due to the numerous external influences (such as temperature), a chemically resistant protective glove in daily use may have a service life that is considerably shorter than the measured break through time.

Skin protection

protective clothing .

8.2.2 Exposure to the environment limited and controlled

Prevent material from entering surface waters, drains or sewers and soil.

8.2.3 Specific notes (Australia):

Select and use respirators in accordance with AS1715/1716.

8.3 Further information for system design and engineering measures

Observe information in section 7. Observe national regulatory requirements.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Property:	Value:	Method:
Appearance		
Physical state	liquid	
Form	Emulsion	
Colour	white	
Odour		
Odour	faint	
Odour limit		
Odour limit	no data available	
pH-Value		
pH-Value	approx. 5 - 8 at 25 °C (100 %)	(Indicator strips)
Melting point/freezing point		
Melting point / melting range	-1 °C	
Initial boiling point and boiling range		
Boiling point / boiling range	100 °C	
Flash point		
Flash point	> 100 °C	(ISO 3679)
Sustained combustibility	not applicable	
Evaporation rate		
Evaporation rate	no data available	
Upper/lower flammability or explosive limits		
Lower explosion limit (LEL)	no data available	
Upper explosion limit (UEL)	no data available	
Vapour pressure		
Vapour pressure	23 hPa / 20 °C	
Solubility(ies)		
Water solubility / miscibility	completely miscible	
Vapour density		
Relative gas/vapour density	No data known.	
Relative Density		
Relative Density	0.95	
	(Water / 4 °C = 1,00)	
Density	0.95 g/cm ³	
Partition coefficient: n-octanol/water		
Partition coefficient: n-octanol/water	No data known.	
Auto-ignition temperature		
Ignition temperature	395 °C	
Viscosity		
Viscosity (dynamic)	ca. 12 mPa.s at 25 °C	
Molecular mass		
Molecular mass	not applicable	

9.2 Other information

Explosion Limits: Explosion limits for released ethanol: 3.5 - 15%(V).

SECTION 10: Stability and reactivity

10.1 – 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

Relevant information can possibly be found in other parts of this section.

10.4 Conditions to avoid

Heat, open flames, and other sources of ignition.

10.5 Incompatible materials

Reacts with: basic substances and acids . Reaction causes the formation of: ethanol .

10.6 Hazardous decomposition products

By hydrolysis: ethanol . The following applies for the silicone content of the substance: Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

11.1.1 Acute toxicity

Assessment:

For similar products no indications for a specific hazard due to aerosol inhalation were identified in animal tests. However, inhalation of respirable aerosol should be avoided.

Product details:

Route of exposure	Result/Effect	Species/Test system	Source
Oral	LD50: > 2000 mg/kg The assessment is made under consideration of relevant data on ingredients.	Rat	Conclusion by analogy

11.1.2 Skin corrosion/irritation

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.3 Serious eye damage / eye irritation

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.4 Respiratory or skin sensitization

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.5 Germ cell mutagenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.11 Further toxicological information

Hydrolysis product / impurity: Ethanol (64-17-5) is readily absorbed at all exposure routes. Ethanol may cause irritation of eyes and mucosa, trigger dysfunction of the central nervous system and cause nausea as well as dizziness. Chronic exposure to high amounts of ethanol may cause damage to liver and central nervous system.

SECTION 12: Ecological information

12.1 Toxicity

Assessment:

According to current knowledge adverse effects on water purification plants are not expected.

12.2 Persistence and degradability

Assessment:

Contact with water liberates ethanol and silanol- and/or siloxanol-compounds. Silicone content: biologically not degradable. Elimination by adsorption to activated sludge. The hydrolysis product (Ethanol) is readily biologically degradable.

Data on substances:

Product of hydrolysis (Ethanol):

Ethanol is readily biodegradable.

12.3 Bioaccumulative potential

Assessment:

Bioaccumulation is not expected to occur.

12.4 Mobility in soil

Assessment:

Silicone content: Absorbed by floating particles. Separation by sedimentation.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

none known

SECTION 13: Disposal considerations

13.1 Waste treatment methods

13.1.1 Material

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.1.2 Uncleaned packaging

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

SECTION 14: Transport information

14.1 – 14.4 UN number; UN proper shipping name; Transport hazard class(es); Packing group

Land transport ADG Code (road and rail):

Valuation: Not regulated for transport

Transport by sea IMDG-Code:

Valuation: Not regulated for transport



Safety Data Sheet

Version: 1.0 (AU)

Q-Coat Water Repellent Penetrating Sealer

Date of print: 11.12.2019

Date of last alteration: 11.12.2019

Air transport ICAO-TI/IATA-DGR:

Valuation: Not regulated for transport

14.5 Environmental hazards

Hazardous to the environment: no

14.6 Special precautions for user

Relevant information in other sections has to be considered.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk transport in tankers is not intended.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

15.1.1 Poisons Standard (Standard for the Uniform Scheduling of Medicines and Poisons; SUSMP)

Poisons Schedule number:

Not a Scheduled Poison.

Label elements:

SECTION 16: Other information

16.1 Material

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

16.2 Further information:

Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

16.3 Glossary of Terms:

CAS No. - Chemical Abstracts Service Registry Number

UN No. - United Nations Dangerous Goods Number

ADG Code - Australian Dangerous Goods Code for the Transport of Dangerous Goods by Road & Rail

IMDG Code - International Maritime Dangerous Goods Code

IATA Regs - International Air Transport Association (IATA) Dangerous Goods Regulations

NOHSC - Australian National Occupational Health and Safety Commission (Note: NOHSC documents are now published by Safe Work Australia)

OEL - Occupational exposure limit in Great Britain

AGW - Occupational exposure limit in Germany

ES_AU - Occupational exposure standard in Australia

- End of Safety Data Sheet -