



# X280™ DENSI-PROOF™ REO PROTECT™

## Technical Data Sheet

Issued: 2nd June 2018  
Document #: 112\_V2L  
Page 1 of 2



## PERMANENT ENGINEERED PROTECTION FOR CONCRETE & STEEL REINFORCEMENT

### Description & Uses

X280 Densi-Proof Reo Protect™ effectively prevents conditions that create and/or promote corrosion activity, significantly retarding rust producing reactions.

### Features and Benefits

- Prevents or Retards Any Future Corrosion
- Retards Existing Corrosion
- Significantly Densifies Concrete
- Internally Waterproofs Concrete
- Makes Concrete More Durable
- Diminishes Permeability
- Improves Surface Bondability
- Restricts Vapour Transmission
- Preserves Concrete's Integrity
- Eliminates Internal Water Migration
- Resists Freeze-Thaw Damage
- Adds Surface Abrasion Resistance
- Decreases Dusting Potential
- Increases Acid / Chemical Resistance
- Lowers Chemical Reaction Potential

### Physical and Chemical Properties

|  |                                    |   |                               |
|--|------------------------------------|---|-------------------------------|
| Appearance:                              | Low viscosity cloudy-white liquid. | Flammability or Explosive Limits:                                     | Not applicable.               |
| Odour:                                   | Almost none.                       | Relative Density:   | Ca. 1.10 @ 20°C.              |
| pH:                                      | Ca. 11.4                           | Solubility:   | Fully miscible in water.      |
| Initial Boiling Point/<br>Boiling Range: | > 100°C @ 760 mm Hg.               | Auto-ignition<br>Temperature:   | Product is not self-igniting. |
| Flash-point:                             | Not applicable.                    | Viscosity:  | Low.                          |
| Flammability<br>(solid, gas):            | Not applicable.                    | Volatile Organic<br>Compounds<br>(VOC) Content;<br>Per Cent Volatile: | 0.0 % w/w.<br>Ca. 0 % w/w.    |

### Recommended Substrate Conditions & Preparation

**Freshly Placed Concrete:** One application @ 5m<sup>2</sup> per litre.

**Existing Concrete:** Discuss with your representative

#### Important Notes:

1. Wax, paint, curing compounds or a burnished surface restricting access to concrete's interior must be chemically or mechanically removed for X280 Densi-Proof Reo Protect™ to penetrate and work properly.
2. Areas of high porosity have a faster penetration rate. These areas appear dry immediately after spraying and will require additional product.
3. Do not apply if the ambient temperature is over 34°C Plan to apply in the cool of the late afternoon or early morning. Mist wet the surface before applying in hot windy conditions.
4. Do not apply if raining or rain is expected within 3 hours of application completion. If rain falls on treated area within 3 hours

of application call Oxtek Head Office for instruction and advice.

5. Before applying any paint, adhesives or any other coatings, wait 24 hours after application with X280 Densi-Proof Reo Protect™. Pressure wash or sand and clean, then check visually to be satisfied purging has completed (If required a second or subsequent coats may be required). Always follow coating manufactures surface requirements.

6. X280 Densi-Proof Reo Protect™ may etch glass/tiles or dull brushed and shiny aluminum and can be difficult to remove from other surfaces once it dries. Cover and mask surrounding surfaces or rinse immediately if sprayed.

7. X280 Densi-Proof Reo Protect's™ spray mist is not hazardous to breathe. However, we do recommend the use of a face mask during application.

Refer to MSDS [www.oxtek.com.au](http://www.oxtek.com.au)



# X280™ Densi-Proof™ Reo Protect™

## Technical Data Sheet

### Application Guide

Issued: 2nd June 2018  
Document #: 112 V2L  
Page 2 of 2

Available in 15, 200 and 1000 litre containers.

#### On Already-Set Concrete:

Note: In hot climates, mist-wet the surface with water and remove any puddles prior to application. Apply X280 Densi-Proof Reo Protect™. Apply with a low-pressure non-atomizing, spray apparatus such as a pump-tank or battery pack sprayer. Holding spray tip (eg .019" - .024") 150mm from surface, apply X280 Densi-Proof Reo Protect™ at minimum rate of 5m<sup>2</sup> per litre with an overlapping spray pattern of 50%.

Begin application at the lowest elevation. For example, walls and slopes should be applied side to side, from the bottom up. Using a soft broom sweep and spread out puddled product as it penetrates.

Do not allow X280 Densi-Proof Reo Protect™ to puddle dry on the surface. If product gels on the surface remove with a squeegee.

#### As a Cure Method at Time of Pour:

Apply with a low-pressure non-atomizing, spray apparatus such as a pump-tank or battery pack sprayer. X280™ Densi-Proof Reo Protect is ideally applied to the newly-poured concrete surface as soon as is practical following its surface finishing phase. Should conditions require the surface to be walked on, for application, concrete should be allowed the time to adequately set, so as not to imprint or mar its surface during application. Recommended minimum coverage rate as a cure method is 5m<sup>2</sup> per litre with an overlapping spray pattern of 50%.

Available in 15, 200 and 1000 litre containers.

### Warranty Registration

Call your Oxtek Solutions office to arrange personal assistance and advice anywhere in Australia or New Zealand. We have technical expertise and experience to help and consult on your next project or help your existing project maintain time and budget. An issued warranty is project specific and will require us to provide consultation and a registered specification number.

Warranties are not available on concrete older than 15 years, call **+61 3 9798 7534** for advice today.

Email Head Office - [reception@oxtek.com.au](mailto:reception@oxtek.com.au)  
[www.oxtek.com.au](http://www.oxtek.com.au)

### On site - In Office

We can save you time and money, call now to arrange face to face personal assistance and advice any where in Australia or New Zealand. We have the expertise, answers and experience to help and consult on your next project or help your existing project maintain time and budget.  
Australia **1300 698 351**

